



## Prism Printer Specifications

Item	Description
<b>Printing Speed</b>	0.65 inches/second @ 300 x 300 dpi, typical 0.45 inches/second @ 300 x 600 dpi, typical
<b>Printing Direction</b>	Images are printed from a top to bottom orientation as the media is moving out of the machine.
<b>Printing Modes</b>	Single-pass (standard) and double-pass (monochrome ribbon only) for improved print quality on some media types.
<b>Print Quality</b>	300x300 or 300x600 dpi (11.8 dots per mm)
<b>Media Types</b>	120mm CD and DVD media with thermal protective layers
<b>Standard Ribbon Color</b>	Black, Red, and Blue monochrome ribbons
<b>Multi-Color Ribbon</b>	3-color (CMY) panel ribbon
<b>Ribbon Capacity</b>	Monochrome black = 2100 discs Monochrome red = 2100 discs Monochrome blue = 2100 discs 3-color panel = 500 discs
<b>Physical Properties</b>	6.0" H x 8.5" W x 14.0" D (15.24 cm x 21.59 cm x 35.56 cm) 18 pounds (8.2 kg)
<b>Interface</b>	USB 1.0, Parallel, Serial (USB supported with Windows 2000 Professional with SP4; Windows XP Professional with SP2 or higher; Windows Server 2003)
<b>Power</b>	100-240 VAC, 50-60 Hz, 1.10-0.55 Amps auto ranging
<b>Operating Temperature</b>	60° F to 90° F (15.5° C to 35° C)
<b>Relative Humidity</b>	30% to 80% non-condensing
<b>System Requirements</b>	Pentium 450 (1 GHz or higher recommended). 256 MB RAM (512 MB or higher recommended) Windows 2000 Professional with SP4; Windows XP Professional with SP2 or higher, or Server 2003